

GRADE 300

CLASSIC



THE
SYMPHONY
COLLECTION™

Resilience^{SR}
ENDURING PROTECTION

CLASSIC



Mustang
SCL-109



Chamomile
SCL-103



Cashew
SCL-011



Saffron
SCL-035



Persimmon
SCL-030




Cayenne
SCL-012




Saddle
SCL-034



American Beauty
SCL-003



Tandoor
SCL-114



Rouge
SCL-032



Brick
SCL-007



Claret
SCL-015



Burgundy
SCL-010



British Tan
SCL-008



Rodeo
SCL-112



Mocha
SCL-026



Hazelnut
SCL-021



Fudge
SCL-018




Chocolate
SCL-014




Marshmallow
SCL-108



White
SCL-042



Creamery
SCL-104



Kilimanjaro
SCL-024



Doe
SCL-016




Chamois
SCL-102



Buff
SCL-009



Papyrus
SCL-029




Stone
SCL-040



Taupe
SCL-041



Sage
SCL-036




Granite
SCL-019



Celery
SCL-013



Scallion
SCL-113




Bayou
SCL-101



Oregano
SCL-110



Orchard
SCL-028




Spruce
SCL-039



Water
SCL-115



Fog
SCL-106




Currant
SCL-105



Iris
SCL-022




Grape
SCL-020



Pewter
SCL-031




Reef
SCL-111



Lake
SCL-107



Blue Ridge
SCL-006



Admiral
SCL-001



Navy
SCL-027



Black
SCL-005

CLASSIC

APPLICATIONS Hospitality, Healthcare, Contract, Education, Marine, Automotive, RV and Residential

GENERAL SPECIFICATIONS

Width 54"
Roll Size 40 Yards
Weight 29 Ounces per Linear Yard
Backing 100% Brushed Polyester Knit

PERFORMANCE SPECIFICATIONS

Abrasion Resistance 500,000+ Double Rubs per ASTM D 4157-10 Wyzenbeek / CFFA-1A
Mildew Resistance Pass per ASTM G21-09 (2002) / CFFA-120
Anti-Bacterial Pass per AATCC 147-2004 / CFFA-300
Anti-Microbial Pass per ASTM G21-09 (2002) / CFFA-120
Ultra Violet Resistance 650 Hours per ASTM G154 / CFFA-2
Cold Crack -20° F per FTMS 191 A TM5874/CFFA-6a-2007
Stain Resistance with Resilience^{SR}
Sulfide Stain Resistance

FLAMMABILITY REQUIREMENTS *

California Fire Code Technical Bulletin No. 117, Section E
UFAC Class 1
BIFMA
NFPA 260
MVSS 302
Boston Fire Department Code Test BFD-IX-1
Port Authority of New York / New Jersey
IMO A.652 (16) 8.2 and 8.3
ASTM E84: Class 1 or A Rating

CLEANING INSTRUCTIONS

Prompt cleaning is always recommended. Ordinary dirt and stains can be removed with a mild soap and water. Rinse the cleaned area with clean water and dry with a lint-free cloth. Classic will resist, without serious discoloration, the repeated actions of normal dilutions of non-abrasive chlorine or ammonia-based cleaners.

Stain Resistant CFFA-141

Ketchup	5
Mayonnaise	5
Soy Sauce	5
Butter	5
Tea	5
Whiskey	5
Coffee	5
Soda	5
Blood	5
Urine	5
Iodine / Betadine	5
Mascara	5
Suntan Lotion	5
Hairspray	5
Lipstick	5
Liquid Foundation	4.5
Motor Oil	5

Grading: Class 5 - Excellent;
Class 4 - Good; Class 3 - Fair;
Class 2 - Poor; Class 1 - Very Poor



Resilience^{SR} represents the latest technology in Faux Leather and Vinyl Protection, enhancing performance where it is needed the most:

STAIN RESISTANCE: With proper care, materials treated with **Resilience^{SR}** can be easily cleaned and will guard against stains maintaining the desired surface appearance for years to come.

ANTI-MICROBIAL & ANTI-BACTERIAL PROTECTION: Products treated with **Resilience^{SR}** are engineered to inhibit bacterial growth, as well as fungus, mold and spores, resulting in a more hygienic environment.

ABRASION RESISTANCE: **Resilience^{SR}** provides additional wear properties and surface durability to any Vinyl or Faux Leather, thereby increasing the life of the material.

Resilience^{SR} is not visible, and does not affect the hand of the material. **Resilience^{SR}** is engineered to last, even after repeated cleaning and wear. Specify **Resilience^{SR}** for the most demanding healthcare and hospitality applications.

